コレヘソヒマ



Espresso

The Slayer Espresso machine is the ultimate coffee professionals tool.

The Espresso provides the control you need to Make Coffee Better. This machine provides flow rate control via patented needle-valve technology, an independent brew tank per group, for impeccable temperature stability and a dedicated tank for unlimited steam capacity. The Espresso is unmatched in innovative technologies and allows you to extract espresso that is unparalleled in flavor and mouthfeel.

Flavor Profiling

Manual operation of 3-position actuator allows total control.

Patented Needle Valve

Meter the introduction of water to the coffee bed for ultimate sweetness and syrupy body.

Pre-heat Tank

Unlimited steam and ultimate brew temperature stability.

Pre-Brew Timers

Automatic pre-brew wetting stage.

Custom Options

Personalize with distinct body panel colors, metal finishes and wood sets (actuators, handles and cuprails).

Shot Mirror

Improves visibility during extraction.



Essential Features

- Patented Needle Valve Grind finer with restricted flow rate during "pre-brew" phase
- Flavor Profiling Manual operation of 2-position actuator allows total control
- Custom Options Personalize with unique powder coat options, chrome or black nickel plating and wood
- Pre-heat Tank Unlimited steam and ultimate brew temperature stability
- Independent brew tanks
- PID temperature control, adjustable in 0.1° increments
- Electronic V3 grouphead rated to 1 million cycles
- Commercial portafilter with 58mm, 18-gram basket®
- Nanotech-coated precision shower screens
- Handcrafted wood handles and actuators
- · Hot water tap with mixing valve
- External rotary pump
- Shot Mirror

Specifications (2-group | 3-group)

- Width: 30.5 | 40.5 in / 77.5 | 103 cm
- **Depth:** 26.5 | **26.5** in / 67.5 | **67.5** cm
- **Height:** 17 | **17** in / 43.5 | **43.5** cm
- Weight: 220 | 305 lbs / 100 | 139 kg (tanks filled)
- Brew tanks: 1.7 liters, 600 watts
- Pre-heat tank: 3.3 | 5.4 liters, 1.000 watts
- Steam tank: 7.4 | 12 liters, 3,500 | 4,500 watts
- Single-phase power: 220-240 V, 50/60 Hz, 26 A | 35 A; 5.7-6.9 | 7.3-8.7 kW
- Three-phase power (optional): 380-415 V3N, 50/60 Hz; 17 A | **22 A**; 5.7-6.9 | **7.3-8.7** kW

